

**10316070011 | 3 carbide rotary burrs, Ø 3 - 4 - 6 mm  
Length 80 mm, Normal teeth with chip breaker**

High-performance monobloc rotary burr that can withstand the majority of metals and composite metals. The 80 mm length allows special locksmith use for opening lock cylinders.



- Cylindrical shank
- Chip breaker teeth
- Carbide head

3 Domed Cylindrical rotary burrs Ø 3 Ø 4 Ø 6 L 80 mm



**Machine**



**Application**

<b>K</b>	<b>M</b>	<b>N</b>	<b>P 1</b>
K- Ferrous Cast iron with Short Chips	M- Stainless steels	N- Non- ferrous alloys	P1- Unrealized steels

**Features**



**Properties and benefits**

- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + Chip-breaking teeth: teeth designed for their high versatility, diamond cutting for the excellent breaking up of chips. ➡ Enables the effective filing of the majority of metals, excellent chip breaking, and neat surface conditions.
- + Tungsten carbide head: ground in a grade of carbide especially suited for high rotation speeds. ➡ Enables an excellent throughout rate and very high resistance to wear, suitable for very high rotation speeds in the majority of metals.

**Données de gestion :**

PCB : 1 / Kilogram. : 0,090 / Dimensions : 0165x0020x0050 mm / EAN : 3221912377029