


Fast and long-lasting countersinking bit for stainless steels, high-strength steels, cast irons, and aluminiums.



- 90° milling angle
- Cylindrical shank
- 5% cobalt HSS
- Head with 3 cutting edges

Countersinking bits Ø 6.3 - 8.3 - 10.4 - 12.4 - 16.5 - 20.5 mm Plastic case

Machine



Application

K	M 1	N	P 1	P 2
K- Ferrous Cast iron with Short Chips	M1- austenitic stainless steels	N- Non- ferrous alloys	P1- Unrealized steels	P2- Weakly allied steels

Features



Properties and benefits

- + 90° milling angle : For 90° chamfering operation. ➡ For making 90° chamfering to down screw and/or rivet heads.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².
- + Head with 3 cutting edges: tool geometry designed with 3 cutting edges. ➡ Enables the excellent distribution of the cutting force and a neat surface condition.

Données de gestion :

PCB : 1 / Kilogram. : 0,295 / Dimensions : 0150x0105x0045 mm / EAN : 3221910899455