

Drilling of steels and stainless steels. Comfort and cutting speed, prolonged service life.




- Especially for high-strength steels, stainless steels and cast irons
- Maximum long life
- Incredibly fast milling
- Made in France

- Weldon shank
- High-speed steel
- TiAlN coating



Machine



Application

K	M 1	P 2	P 3
K- Ferrous Cast iron with Short Chips	M1- austenitic stainless steels	P2- Weakly allied steels	P3- strong alloy steels

Features

HSS	TiAlN COATED	TIVOLY NORM	WELDON 19mm		Z 4-14
------------	---------------------	--------------------	--------------------	--	---------------

Properties and benefits

- + Weldon shank: cylindrical shank with 3/4" flats. ⚙️ Particularly suited for the attachment of tools to drills with a magnetic base.
- + High-speed steel: HSS substrate ⚙️ For general use in steels and cast irons up to 950 N/mm²
- + TiAlN coating: TiAlN base, thickness 2/4µm, hardness 3000HV, coefficient of friction 0.4, heat resistance 900°C. ⚙️ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. Versatile uses.

Code	EAN	Ø	Internal Ø	d2	L	l	Qty	PCB
10370011200	3221910824945	12	6	3/4"	60	30	1	1
10370011300	3221910824952	13	6	3/4"	60	30	1	1
10370011400	3221910824969	14	6	3/4"	60	30	1	1
10370011500	3221910824976	15	6	3/4"	60	30	1	1
10370011600	3221910824983	16	7	3/4"	60	30	1	1
10370011700	3221910824990	17	8	3/4"	60	30	1	1
10370011800	3221910825003	18	9	3/4"	60	30	1	1
10370011900	3221910825010	19	10	3/4"	60	30	1	1
10370012000	3221910825027	20	11	3/4"	60	30	1	1
10370012100	3221910825034	21	12	3/4"	60	30	1	1
10370012200	3221910825041	22	13	3/4"	60	30	1	1
10370012300	3221910825058	23	14	3/4"	60	30	1	1
10370012400	3221910825065	24	15	3/4"	60	30	1	1
10370012500	3221910825072	25	16	3/4"	60	30	1	1
10370012600	3221910825089	26	17	3/4"	60	30	1	1
10370012700	3221910825096	27	18	3/4"	60	30	1	1
10370012800	3221910825102	28	19	3/4"	60	30	1	1
10370012900	3221910825119	29	20	3/4"	60	30	1	1
10370013000	3221910825126	30	21	3/4"	60	30	1	1

Drilling of steels and stainless steels. Comfort and cutting speed, prolonged service life.

10370013100	3221910825133	31	22	3/4"	60	30	1	1
10370013200	3221910825140	32	23	3/4"	60	30	1	1
10370013300	3221910825157	33	24	3/4"	60	30	1	1
10370013400	3221910825164	34	25	3/4"	60	30	1	1
10370013500	3221910825171	35	26	3/4"	60	30	1	1
10370013600	3221910825188	36	27	3/4"	60	30	1	1
10370013700	3221910825195	37	28	3/4"	60	30	1	1
10370013800	3221910825201	38	29	3/4"	60	30	1	1
10370013900	3221910825218	39	30	3/4"	60	30	1	1
10370014000	3221910825225	40	31	3/4"	60	30	1	1
10370014100	3221910825232	41	32	3/4"	60	30	1	1
10370014200	3221910825249	42	33	3/4"	60	30	1	1
10370014300	3221910825256	43	34	3/4"	60	30	1	1
10370014400	3221910825263	44	35	3/4"	60	30	1	1
10370014500	3221910825270	45	36	3/4"	60	30	1	1
10370014600	3221910825287	46	37	3/4"	60	30	1	1
10370014700	3221910825294	47	38	3/4"	60	30	1	1
10370014800	3221910825300	48	39	3/4"	60	30	1	1
10370014900	3221910825317	49	40	3/4"	60	30	1	1
10370015000	3221910825324	50	41	3/4"	60	30	1	1