

A hand-held reamer that accurately calibrates a cylindrical hole (bore) made with a drill bit. Blade with conical entry. Large adjustment range.



■ High-speed steel

Machine



Application



P1- Unrealized steels

P2- Weakly allied steels

P3- strong alloy steels

Features



Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Ø	d2	L	I	I3	QTY	PCB
10400910809	3221910897789	8-9	4	32	32		1	1
10400910910	3221910643195	9-10	4	32	32		1	1
10400911011	3221910897796	10-11	4	35	35		1	1
10400911112	3221910897802	11-12	6	35	35		1	1
10400911213	3221910897819	12-13,5	6.2	42	42		1	1
10400911315	3221910897826	13,5-15,5	7	50	50		1	1
10400911518	3221910897833	15,5-18	8	60	60		1	1
10400911821	3221910897840	18-21	9	65	65		1	1
10400912124	3221910897857	21-24	10	70	70		1	1
10400912427	3221910897864	24-27,5	11	75	75		1	1
10400912731	3221910897871	27,5-31,5	12	80	80		1	1
10400913137	3221910897888	31,5-37	14.5	90	90		1	1
10400913745	3221910897895	37-45	16	100	100		1	1
10400914555	3221910897901	45-55	20	109	109		1	1