




- Especially for soft steels and plastics
- Compact product
- High-speed steel

Machine



Application



Features



Properties and benefits

- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
105022100120140	3221912303028	BSPG	1/2"	14	DIN 5157	19,00	80	22	2-3	12,00	1	1
105022100140190	3221912303004	BSPG	1/4"	19	DIN 5157	11,80	70	20	2-3	9,00	1	1
105022100180280	3221912302991	BSPG	1/8"	28	DIN 5157	8,80	63	18	2-3	5,50	1	1
105022100340140	3221912303035	BSPG	3/4"	14	DIN 5157	24,50	90	22	2-3	16,00	1	1
105022100380190	3221912303011	BSPG	3/8"	19	DIN 5157	15,25	70	20	2-3	9,00	1	1
105022110000110	3221912303059	BSPG	1"	11	DIN 5157	30,75	125	32	2-3	20,00	1	1
105022110120110	3221912303073	BSPG	1"1/2	11	DIN 5157	45,50	140	32	2-3	29,00	1	1
105022110140110	3221912303066	BSPG	1"1/4	11	DIN 5157	39,50	125	32	2-3	24,00	1	1
105022120000110	3221912303080	BSPG	2"	11	DIN 5157	57,00	160	36	2-3	35,00	1	1