



- Especially for soft steels and plastics
- High-speed steel

**Machine**



**Application**



P1-  
Unrealized  
steels

P2-  
Weakly  
allied  
steels

**Features**



**Properties and benefits**

- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
1050361060075	3221912307712	MF 6	6	0.75	DIN 2181	5,20	50	14	2 > 3	4,90	1	1
1050361080075	3221912307729	MF 8	8	0.75	DIN 2181	7,20	50	18	2 > 3	4,90	1	1
1050361080100	3221912307736	MF 8	8	1	DIN 2181	7,00	56	22	2 > 3	4,90	1	1
1050361100100	3221912307743	MF 10	10	1	DIN 2181	9,00	63	18	2 > 3	5,50	1	1
1050361100125	3221912307750	MF 10	10	1.25	DIN 2181	8,80	70	24	2 > 3	5,50	1	1
1050361120100	3221912307767	MF 12	12	1	DIN 2181	11,00	70	20	2 > 3	7,00	1	1
1050361120125	3221912307774	MF 12	12	1.25	DIN 2181	10,80	70	20	2 > 3	7,00	1	1
1050361120150	3221912307781	MF 12	12	1.5	DIN 2181	10,50	70	20	2 > 3	7,00	1	1
1050361140125	3221912307798	MF 14	14	1.25	DIN 2181	12,80	70	22	2 > 3	9,00	1	1
1050361140150	3221912307804	MF 14	14	1.5	DIN 2181	12,50	70	22	2 > 3	9,00	1	1
1050361160150	3221912307828	MF 16	16	1.5	DIN 2181	14,50	70	22	2 > 3	9,00	1	1
1050361180150	3221912307835	MF 18	18	1.5	DIN 2181	16,50	80	22	2 > 3	9,00	1	1
1050361200150	3221912307842	MF 20	20	1.5	DIN 2181	18,50	80	22	2 > 3	12,00	1	1
1050361220150	3221912307859	MF 22	22	1.5	DIN 2181	20,50	80	22	2 > 3	14,50	1	1
1050361240150	3221912307866	MF 24	24	1.5	DIN 2181	22,50	90	22	2 > 3	14,50	1	1