

1080252 | Flat wood bit - Hexagonal shank - Reinforced body **TECHNIC (Blister)**

Incredibly fast and precise high-performance drill bit for the hardest of woods, thanks to its double chip-breaking cut and its reinforced body, which is particularly suited for large-diameter drilling.



- Especially for hardwoods and terraces
- Especially for large diameters
- Incredibly fast drilling
- Maximum long life
- Quick tool changing


- Carbon steel
- Double chip breaker
- Quick-change shank
- Reinforced body
- Centring point



Machine



Application



Features




Properties and benefits

- + Carbon steel: body designed in a grade of steel designed for thermal processing, enabling excellent power and torque transmission. ➔ Enables the fast and precise cutting of the tools into soft and hard woods. Superior service life.
- + Double chip breaker: cut geometry designed with specially ground cutting edges, combined with a section that enables chip breaking. ➔ Enables the precise and fast cutting of the hardest woods. Especially for drilling large diameters
- + Quick-Change hex attachment: a hexagonal recessed attachment for the quick locking and unlocking of the bit. Compliant with the DIN 3126 E6.3 standard ➔ Enables the quick changing of your bits by doing away with the manual tightening/loosening of the chuck. For drills and screwdrivers.
- + Reinforced body: "oversize" tool body designed in a grade of steel designed for thermal processing, enabling excellent power and torque transmission. ➔ Enables optimal torque transmission, for the effective drilling of the most difficult woods. Maximum lifespan.
- + Centring point: cut designed with a central centring point ➔ Enables the simple centring of the drill for precision work.



1080252 | Flat wood bit - Hexagonal shank - Reinforced body TECHNICAL (Blister)

Incredibly fast and precise high-performance drill bit for the hardest of woods, thanks to its double chip-breaking cut and its reinforced body, which is particularly suited for large-diameter drilling.



Code	EAN	Ø	d2/CM	L	I	lu	QTY	PCB
10802520800	3221910023393	8	6.35	149			1	3
10802521000	3221910023416	10	6.35	152			1	3
10802521200	3221910023423	12	6.35	152			1	3
10802521400	3221910023447	14	6.35	152			1	3
10802521600	3221910023461	16	6.35	152			1	3
10802521800	3221910023485	18	6.35	152			1	3
10802522000	3221910023508	20	6.35	152			1	3
10802522200	3221910023515	22	6.35	158			1	3
10802522300	3221910023522	23	6.35	158			1	3
10802522400	3221910023539	24	6.35	158			1	3
10802522500	3221910023546	25	6.35	158			1	3
10802522600	3221910023553	26	6.35	158			1	3
10802522800	3221910023560	28	6.35	164			1	3
10802523000	3221910023577	30	6.35	164			1	3
10802523200	3221910023584	32	6.35	164			1	1
10802523400	3221910023607	34	6.35	164			1	1
10802523500	3221910023614	35	6.35	164			1	1
10802523600	3221910023621	36	6.35	164			1	1
10802523800	3221910023638	38	6.35	164			1	1
10802524000	3221912331304	40	6.35	164			1	1