

High-performance drill bit for the deep and large diameter drilling of reinforced concrete and harder materials. Fast and long-lasting drilling thanks to its multi-edge cutting inserts



- Especially for reinforced concrete and hard materials
- Deep and through-drilling
- Maximum long life
- Rapid drilling
- Precise drilling

- SDSmax shank
- High-strength steel
- Dust extraction +++
- Pad with 2 cutting edges



Machine



Application



Features



Properties and benefits

- + SDSmax shank: attachment for SDSmax hammer drills (18 mm shank diameter) compliant with the SDSmax label, greater than 3 joules. ➡ Maximum striking power transmission for the simple and fast processing of the most difficult materials. For bits larger than 12 mm.
- + High strength steel body: body designed in a grade of steel designed for thermal processing, enabling excellent power and torque transmission. ➡ Enables optimal power and torque transmission to the head of the tool.
- + Effective dust clearance: body of the tool designed with a large-capacity fluted profile, for the easy extraction of materials. ➡ For optimal and regular evacuation of dust.
- + Cutting insert with 4 cutting edges: carbide cutting insert designed with four cutting edges, distributed force, anti-jamming effect. ➡ Enables the drilling of hard materials and reinforcing rods, thanks to its 4 cutting edges.



| Code | EAN | Ø | d2/CM | L | l | lu | QTY | PCB |
|-------------|---------------|----|---------|-----|-----|----|-----|-----|
| 10906031600 | 3221910863210 | 16 | SDS MAX | 920 | 800 | | 1 | 1 |
| 10906031800 | 3221910863227 | 18 | SDS MAX | 920 | 800 | | 1 | 1 |
| 10906032000 | 3221910227869 | 20 | SDS MAX | 920 | 800 | | 1 | 1 |
| 10906032200 | 3221910227876 | 22 | SDS MAX | 920 | 800 | | 1 | 1 |
| 10906032500 | 3221910227883 | 25 | SDS MAX | 920 | 800 | | 1 | 1 |
| 10906033200 | 3221910227890 | 32 | SDS MAX | 920 | 800 | | 1 | 1 |
| 10906034000 | 3221910863234 | 40 | SDS MAX | 920 | 800 | | 1 | 1 |