

## 1096054 | Concrete drill bits - Carbide centring tip - Tri-flat cylindrical shank - SLR graduated TECHNIC (Plastic sleeve)

High-performance drill bit for the incredibly fast and precise drilling of reinforced concrete and hard materials, thanks to its three-faceted carbide cutting insert.





- Especially for reinforced concrete and hard materials
- Incredibly fast drilling
- Maximum long life
- Anti-rotation attachment
- Ultra-precise/controllable drilling
- Tri-flat shank
- High-strength steel
- Multi-facetted
- Centring point
- SLR laser graduation

## Machine













**Features** 













## Properties and benefits

- + Tri-flat shank: cylindrical shank with 3x 120° flats, for 3-piece drill chucks. 

  Enables maximum torque transmission Prevents the rotation of the bit in the chuck. Specially adapted for through-holes.
- + High strength steel body: body designed in a grade of steel designed for thermal processing, enabling excellent power and torque transmission. Enables optimal power and torque transmission to the head of the tool.
- → Multi-facetted cutting insert: carbide cutting insert designed with multiple facets, promoting the effective splitting of the materials 

  Enables the excellent splitting of materials into dust, thus facilitating their extraction.
- + Centring point: carbide cutting insert designed with an integrated centring point at its centre. 

  Enables the easy centring of the drill, particularly in coarse materials. Excellent drilling precision.
- + SLR laser graduation: laser graduation on the cutting part of the drill bit. 

  □ Laser graduation allows you to control your drilling depth while the bit is rotating.



| Code        | EAN           | Ø  | d2/CM | L   |    | lu QTY | PCB |
|-------------|---------------|----|-------|-----|----|--------|-----|
| 10960540300 | 3221912031761 | 3  | 2.8   | 60  | 34 | 1      | 3   |
| 10960540400 | 3221912031778 | 4  | 3.8   | 75  | 40 | 1      | 3   |
| 10960540500 | 3221912031785 | 5  | 4.8   | 85  | 50 | 1      | 3   |
| 10960540600 | 3221912031792 | 6  | 5.8   | 100 | 60 | 1      | 3   |
| 10960540700 | 3221912031808 | 7  | 5.8   | 100 | 60 | 1      | 3   |
| 10960540800 | 3221912031815 | 8  | 7.6   | 120 | 72 | 1      | 3   |
| 10960540900 | 3221912031822 | 9  | 7.6   | 120 | 72 | 1      | 3   |
| 10960541000 | 3221912031839 | 10 | 8.8   | 120 | 72 | 1      | 3   |
| 10960541200 | 3221912031846 | 12 | 10    | 150 | 92 | 1      | 1   |