

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision

- High-speed steel

Machine



Application

N	P 1	P 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed dechlorate steels

Features

HSS	BRIGHT UNCOATED	NFE 74001	M MF	38,1	6g
------------	------------------------	------------------	-------------	-------------	-----------

Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Item number M3	EAN (13 digits)	M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No.
1100041080125	3221910553425		M8	1,25	38.1	13	
1100041090125	3221910553432		M9	1,25	38.1	13	
1100041100150	3221910553463		M10	1,5	38.1	13	
1100041110150	3221910553487		M11	1,5	38.1	13	
1100041120175	3221910553524		M12	1,75	38.1	13	
1100041130175	3221910553555		M13	1,75	38.1	13	
1100041140200	3221910553593		M14	2	38.1	13	
1100041160200	3221910553616		M16	2	38.1	13	
1100041180250	3221910553647		M18	2,5	38.1	13	
1100041200250	3221910553661		M20	2,5	38.1	13	
1100041100100	3221910553449		MF10	1	38.1	13	
1100041100125	3221910553456		MF10	1,25	38.1	13	
1100041120100	3221910553494		MF12	1	38.1	13	
1100041120125	3221910553500		MF12	1,25	38.1	13	
1100041120150	3221910553517		MF12	1,5	38.1	13	
1100041130150	3221910553548		MF13	1,5	38.1	13	
1100041140100	3221910553562		MF14	1	38.1	13	
1100041140125	3221910553579		MF14	1,25	38.1	13	
1100041140150	3221910553586		MF14	1,5	38.1	13	
1100041160150	3221910553609		MF16	1,5	38.1	13	
1100041180150	3221910553623		MF18	1,5	38.1	13	
1100041180200	3221910553630		MF18	2	38.1	13	
1100041200150	3221910553654		MF20	1,5	38.1	13	