

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision
  
- High-speed steel

**Machine**



**Application**

<b>N</b>	<b>P</b> 1	<b>P</b> 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed declotage steels

**Features**

<b>HSS</b>	<b>BRIGHT UNCOATED</b>	<b>NFE 74001</b>	<b>M MF</b>	<b>50,8</b>	<b>6g</b>
------------	------------------------	------------------	-------------	-------------	-----------

**Properties and benefits**

- + High-speed steel: HSS substrate → For general use in steels and cast irons up to 950 N/mm<sup>2</sup>



Item number M3	EAN (13 digits) M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No.
1100051160200	3221910709372	M16	2	50.8	17	
1100051180250	3221910709396	M18	2,5	50.8	17	
1100051200250	3221910709419	M20	2,5	50.8	17	
1100051220250	3221910709433	M22	2,5	50.8	17	
1100051240300	3221910709457	M24	3	50.8	17	
1100051270300	3221910709464	M27	3	50.8	17	
1100051180150	3221910709389	MF18	1,5	50.8	17	
1100051200150	3221910709402	MF20	1,5	50.8	17	
1100051220150	3221910709426	MF22	1,5	50.8	17	
1100051240150	3221910709440	MF24	1,5	50.8	17	