

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision

- High-speed steel

Machine



Application

N	P 1	P 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed declotage steels

Features

HSS	BRIGHT UNCOATED	NFE 74001	M MF	63,5
------------	------------------------	------------------	-------------	-------------

Properties and benefits

- + High-speed steel: HSS substrate → For general use in steels and cast irons up to 950 N/mm²



Item number M3	EAN (13 digits) M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No.
1100061240300	3221910709679	M24	3	63.5	20	
1100061270300	3221910709709	M27	3	63.5	20	
1100061300350	3221910709747	M30	3,5	63.5	20	
1100061330350	3221910709754	M33	3,5	63.5	20	
1100061360400	3221910709761	M36	4	63.5	20	
1100061270150	3221910709686	MF27	1,5	63.5	20	
1100061270200	3221910709693	MF27	2	63.5	20	
1100061280150	3221910709716	MF28	1,5	63.5	20	
1100061300150	3221910709723	MF30	1,5	63.5	20	
1100061300200	3221910709730	MF30	2	63.5	20	