

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision
- High-speed steel

Machine



Application

N	P 1	P 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed declotage steels

Features

HSS	BRIGHT UNCOATED	EN 22568	UNC	20-45	2A
------------	------------------------	-----------------	------------	--------------	-----------

Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Item number M3	EAN (13 digits) M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No. pieces per sales unit	PCB By How Much M3
11004710005	3221910713157	5"	40	20	5	1	1
11004710006	3221910713164	6"	32	20	5	1	1
11004710008	3221910713171	8"	32	20	5	1	1
11004710010	3221910713188	10"	24	20	7	1	1
11004710012	3221910713195	12"	24	20	7	1	1
11004710104	3221910713218	1/4"	20	20	7	1	1
11004710516	3221910713249	5/16"	18	25	9	1	1
11004710308	3221910713232	3/8"	16	30	11	1	1
11004710716	3221910713256	7/16"	14	30	11	1	1
11004710102	3221910713201	1/2"	13	38	14	1	1
11004710304	3221910713225	3/4"	10	45	18	1	1