

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision
- High-speed steel

**Machine**



**Application**

<b>N</b>	<b>P</b> 1	<b>P</b> 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed dechlorage steels

**Features**

<b>HSS</b>	<b>BRIGHT UNCOATED</b>	<b>EN 22568</b>	<b>UNC</b>	<b>20-45</b>	<b>2A</b>
------------	------------------------	-----------------	------------	--------------	-----------

**Properties and benefits**

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>



Item number M3	EAN (13 digits)	M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No.
11004710005	3221910713157		5"	40	20	5	
11004710006	3221910713164		6"	32	20	5	
11004710008	3221910713171		8"	32	20	5	
11004710010	3221910713188		10"	24	20	7	
11004710012	3221910713195		12"	24	20	7	
11004710104	3221910713218		1/4"	20	20	7	
11004710516	3221910713249		5/16"	18	25	9	
11004710308	3221910713232		3/8"	16	30	11	
11004710716	3221910713256		7/16"	14	30	11	
11004710102	3221910713201		1/2"	13	38	14	
11004710304	3221910713225		3/4"	10	45	18	