

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision

- High-speed steel

Machine



Application

N	P 1	P 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed declotage steels

Features

HSS	BRIGHT UNCOATED	EN 22568	UNF	20-45	2A
------------	------------------------	-----------------	------------	--------------	-----------

Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Item number M3	EAN (13 digits) M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No. pieces per sales unit	PCB By How Much M3
11004810005	3221910713263	5"	44	20	5	1	1
11004810006	3221910713270	6"	40	20	5	1	1
11004810008	3221910713287	8"	36	20	5	1	1
11004810010	3221910713294	10"	32	20	7	1	1
11004810012	3221910713300	12"	28	20	7	1	1
11004810104	3221910713324	1/4"	28	20	7	1	1
11004810516	3221910713355	5/16"	24	25	9	1	1
11004810308	3221910713348	3/8"	24	30	11	1	1
11004810716	3221910713362	7/16"	20	30	11	1	1
11004810102	3221910713317	1/2"	20	38	10	1	1
11004810304	3221910713331	3/4"	16	45	11	1	1