

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision
- High-speed steel

**Machine**



**Application**

<b>N</b>	<b>P</b> 1	<b>P</b> 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed dechlorage steels

**Features**

<b>HSS</b>	<b>BRIGHT UNCOATED</b>	<b>EN 22568</b>	<b>UNF</b>	<b>20-45</b>	<b>2A</b>
------------	------------------------	-----------------	------------	--------------	-----------

**Properties and benefits**

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>



Item number M3	EAN (13 digits)	M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No.
11004810005	3221910713263		5"	44	20	5	
11004810006	3221910713270		6"	40	20	5	
11004810008	3221910713287		8"	36	20	5	
11004810010	3221910713294		10"	32	20	7	
11004810012	3221910713300		12"	28	20	7	
11004810104	3221910713324		1/4"	28	20	7	
11004810516	3221910713355		5/16"	24	25	9	
11004810308	3221910713348		3/8"	24	30	11	
11004810716	3221910713362		7/16"	20	30	11	
11004810102	3221910713317		1/2"	20	38	10	
11004810304	3221910713331		3/4"	16	45	11	