

High-performance drill bit for the deep and through-drilling of steels, stainless steels, and cast irons.



- Especially for stainless steel and high-strength steels
- Deep drilling
- Rapid drilling
- Tough
- Versatile use
  
- Automatic centring
- Cylindrical shank
- 30° type N flute
- 5% cobalt HSS
- 135° tip



**Machine**



**Application**

<b>M</b> 1	<b>P</b> 1	<b>P</b> 2	<b>P</b> 3
M1- austenitic stainless steels	P1- Unrealized steels	P2- Weakly allied steels	P3- strong alloy steels

**Features**



**Properties and benefits**

- + Split-point grinding:reduction of the drill tip. ➡ Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the required axial load.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm<sup>2</sup>.
- + 135° tip: 135° tip angle for the sharpening of the drill bit. ➡ Suitable for strong and difficult materials. Enables a shorter and stronger cutting edge, thus prolonging the service life.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11405720200	3221912087164	2	2	85	56		1	3
11405720250	3221912087171	2.5	2.5	95	62		1	3
11405720300	3221912087188	3	3	100	66		1	3
11405720350	3221912087195	3.5	3.5	112	73		1	3
11405720400	3221912087201	4	4	119	78		1	3



# 1140572 | Cobalt HSS-E5 (5% cobalt) metal drill bit - Long series - Split point **TECHNIC** (Blister)

High-performance drill bit for the deep and through-drilling of steels, stainless steels, and cast irons.

11405720450	3221912087218	4.5	4.5	126	82	1	3
11405720500	3221912087225	5	5	132	87	1	3
11405720600	3221912087232	6	6	139	91	1	3
11405720800	3221912087249	8	8	165	109	1	1