

# 1142061 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd - Extra long L160 mm - Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 160). Made in France.



- Especially for high-strength steels, stainless steels and cast irons
- Deep drilling
- Precise drilling
- Tough
- Made in France
  
- Conventional point
- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip

## Machine



## Application



## Features



## Properties and benefits

- + Conventional grinding: with a standard point sharpening ➡ Simple and robust, for versatile use. Enables good hole precision and wear resistance.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>
- + 118° tip: 118° tip angle for the sharpening of the drill bit. ➡ Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11420610300	3221910845001	3	3	160	120		1	1
11420610350	3221910845018	3.5	3.5	160	120		1	1
11420610400	3221910845025	4	4	160	120		1	1
11420610450	3221910845032	4.5	4.5	160	120		1	1
11420610500	3221910845049	5	5	160	120		1	1
11420610550	3221910845056	5.5	5.5	160	120		1	1
11420610600	3221910845063	6	6	160	120		1	1