

1142071 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd -Extra long L200 mm -Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 200). Made in France.



- Especially for high-strength steels, stainless steels and cast irons
- Deep drilling
- Precise drilling
- Tough
- Made in France

- Conventional point
- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip

Machine



Application

K 2	K 3	M 1	P 1	P 2
K2- Gray Cast iron	K3- Nodular and GS Cast iron	M1- austenitic stainless steels	P1- Unrealized steels	P2- Weakly allied steels

Features

HSS	STEAM TREATED	NFE 66075	CYL		118°		30°	>10xd	h8
------------	----------------------	------------------	------------	--	-------------	--	------------	-----------------	-----------

Properties and benefits

- + Conventional grinding: with a standard point sharpening ➡ Simple and robust, for versatile use. Enables good hole precision and wear resistance.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²
- + 118° tip: 118° tip angle for the sharpening of the drill bit. ➡ Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11420710300	3221910845070	3	3	200	150		1	1
11420710350	3221910845087	3.5	3.5	200	150		1	1
11420710400	3221910845094	4	4	200	150		1	1
11420710450	3221910845100	4.5	4.5	200	150		1	1
11420710500	3221910845117	5	5	200	150		1	1
11420710550	3221910845124	5.5	5.5	200	150		1	1
11420710600	3221910845131	6	6	200	150		1	1
11420710650	3221910845148	6.5	6.5	200	150		1	1
11420710700	3221910845155	7	7	200	150		1	1
11420710750	3221910845162	7.5	7.5	200	150		1	1
11420710800	3221910845179	8	8	200	150		1	1
11420710850	3221910845186	8.5	8.5	200	150		1	1
11420710900	3221910845193	9	9	200	150		1	1



1142071 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd -Extra long L200 mm -Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 200). Made in France.

11420710950	3221910845209	9.5	9.5	200	150	1	1
11420711000	3221910845216	10	10	200	150	1	1