

1142081 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd -Extra long L250 mm -Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 250). Made in France.



- Especially for high-strength steels, stainless steels and cast irons
- Deep drilling
- Precise drilling
- Tough
- Made in France

- Conventional point
- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip

Machine



Application



Features



Properties and benefits

- + Conventional grinding: with a standard point sharpening ➡ Simple and robust, for versatile use. Enables good hole precision and wear resistance.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²
- + 118° tip: 118° tip angle for the sharpening of the drill bit. ➡ Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11420810350	3221910845223	3.5	3.5	250	187	1	1	
11420810400	3221910845230	4	4	250	187	1	1	
11420810450	3221910845247	4.5	4.5	250	187	1	1	
11420810500	3221910845254	5	5	250	187	1	1	
11420810550	3221910845261	5.5	5.5	250	187	1	1	
11420810600	3221910845278	6	6	250	187	1	1	
11420810650	3221910845285	6.5	6.5	250	187	1	1	
11420810700	3221910845292	7	7	250	187	1	1	
11420810750	3221910845308	7.5	7.5	250	187	1	1	
11420810800	3221910845315	8	8	250	187	1	1	
11420810850	3221910845322	8.5	8.5	250	187	1	1	
11420810900	3221910845339	9	9	250	187	1	1	
11420810950	3221910845346	9.5	9.5	250	187	1	1	



1142081 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd -Extra long L250 mm -Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 250). Made in France.

11420811000	3221910845353	10	10	250	187	1	1
11420811050	3221910845360	10.5	10.5	250	187	1	1
11420811100	3221910845377	11	11	250	187	1	1
11420811200	3221910845391	12	12	250	187	1	1
11420811300	3221910845414	13	13	250	187	1	1