

1143704 | Fully ground monobloc HSS metal drill bit - Split point - Hexagonal shank **TECHNIC (Plastic sleeve)**

Special high-performance sheet metal and tubing drill bit, compact and strong thanks to its monobloc design.




- Especially for sheet metal and tubing
- Monobloc tool
- Rapid drilling
- Quick tool changing

- Automatic centring
- 6.35 mm hexagonal shank
- 30° type N flute
- High-speed steel
- 118° tip

Machine



Application



Features



Properties and benefits

- + Split-point grinding:reduction of the drill tip. ➡ Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the required axial load.
- + 6.35 mm hexagonal shank / DIN 3126 C 6.3 standard: geometric characteristics comply with dimensional standards. ➡ Enables a perfect hold with bit-holders.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²
- + 118° tip: 118° tip angle for the sharpening of the drill bit. ➡ Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11437040300	3221910881450	3	6.35	38	16		1	1
11437040350	3221910881467	3.5	6.35	40	18		1	1
11437040400	3221910881474	4	6.35	44	20		1	1
11437040450	3221910881481	4.5	6.35	46	24		1	1
11437040500	3221910881498	5	6.35	50	26		1	1
11437040550	3221910881504	5.5	6.35	50	26		1	1
11437040600	3221910881511	6	6.35	50	26		1	1
11437040650	3221910881528	6.5	6.35	50	30		1	1
11437040700	3221910881535	7	6.35	50	30		1	1
11437040800	3221910881542	8	6.35	51	32		1	1
11437040850	3221910881559	8.5	6.35	53	33		1	1
11437040900	3221910881566	9	6.35	53	33		1	1
11437041000	3221910881573	10	6.35	54	38		1	1