1143741 | Fully ground HSS metal drill bit -DIN1897 -h8 -Special sharpening for metal sheet

Drilling and blunting of steel and stainless steel sheets.





- **Especially for sheet metal and tubing**
- **Ultra-precise drilling**
- **Rapid drilling**
- **Tough**
- **Made in France**

- Sheet metal cutting
- Cylindrical shank
- 30° type N flute
- High-speed steel

Machine



Application

P 1 P 2

Features

HSS · BRIGHT UNCOATED · DIN 1897 · CYL · N TYPE · 30° · 1xd · h8

Properties and benefits

- Sheet metal cutting: with centring tip and lip. ➔ Circular and burr-free drilling of thin sheet metals. Suitable for the misalignment of weld points.
- Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➔ Enables versatile use on portable electrical tools and CNC machine tools.
- 30° type N flute: normal flute profile with a 30° helix angle. ➔ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- High-speed steel: HSS substrate ➔ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11437410300	3221910213640	3	3	46	16		1	10
11437410350	3221910213664	3.5	3.5	52	20		1	10
11437410400	3221910213671	4	4	55	22		1	10
11437410420	3221910213688	4.2	4.2	55	22		1	10
11437410450	3221910213695	4.5	4.5	58	24		1	10
11437410500	3221910213701	5	5	62	26		1	10
11437410550	3221910213725	5.5	5.5	66	28		1	10
11437410600	3221910213732	6	6	66	28		1	10
11437410800	3221910213749	8	8	79	37		1	10
11437411000	3221910213756	10	10	89	43		1	5