

1145311 | Fully ground HSS metal drill bit - TiN-coated - Split point - Tri-flat shank **TECHNIC (Tube)**

High-performance drill bit for the intensive drilling of strong metals and stainless steels, superior lifespan thanks to its TITANIUM coating. Precise and rapid drilling.



- Especially for stainless steel and high-strength steels
- Superior long life
- Rapid drilling
- Precise drilling
- Anti-rotation attachment

- Automatic centring
- Tri-flat shank
- High-speed steel
- 135° tip
- TiN coating



Machine



Application

K 2	K 3	M 1	P 1	P 2
K2- Gray Cast iron	K3- Nodular and GS Cast iron	M1- austenitic stainless steels	P1- Unrealized steels	P2- Weakly allied steels

Features



Properties and benefits

- + Split-point grinding:reduction of the drill tip. ⚙️ Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the required axial load.
- + Tri-flat shank: cylindrical shank with 3x 120° flats, for 3-piece drill chucks. ⚙️ Enables maximum torque transmission Prevents the rotation of the bit in the chuck. Specially adapted for through-holes.
- + High-speed steel: HSS substrate ⚙️ For general use in steels and cast irons up to 950 N/mm²
- + 135° tip: 135° tip angle for the sharpening of the drill bit. ⚙️ Suitable for strong and difficult materials. Enables a shorter and stronger cutting edge, thus prolonging the service life.
- + TiN coating: TiN base, thickness 2/4µm, hardness 2300HV, coefficient of friction 0.4, heat resistance 600°C. Protects against abrasion, oxidation, adhesion. ⚙️ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. General use.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11453110100	3221912238566	1	1	34	12	12	1	10
11453110150	3221912238580	1.5	1.5	40	18	18	1	10
11453110200	3221912238597	2	2	49	24	24	1	10
11453110250	3221912238603	2.5	2.5	57	30	30	1	10
11453110300	3221912238610	3	3	61	33	33	1	10
11453110320	3221912238627	3.2	3.2	65	36	36	1	10

1145311 | Fully ground HSS metal drill bit - TiN-coated - Split point - Tri-flat shank **TECHNIC (Tube)**

High-performance drill bit for the intensive drilling of strong metals and stainless steels, superior lifespan thanks to its TITANIUM coating. Precise and rapid drilling.

11453110350	3221912238634	3.5	3.5	70	39	39	1	10
11453110400	3221912238641	4	4	75	43	43	1	10
11453110420	3221912239594	4,20	4.2	75	43		1	10
11453110450	3221912238658	4.5	4.5	80	52	52	1	10
11453110480	3221912238665	4.8	4.8	86	52	52	1	10
11453110500	3221912238672	5	5	86	52	52	1	10
11453110520	3221912238689	5.2	5.2	86	52	52	1	10
11453110550	3221912238696	5.5	5.5	93	57	57	1	10
11453110600	3221912238702	6	6	101	63	63	1	10
11453110620	3221912238719	6.2	6.2	101	63	63	1	10
11453110650	3221912238726	6.5	6.5	101	63	63	1	10
11453110700	3221912238733	7	7	109	69	69	1	10
11453110750	3221912238740	7.5	7.5	109	69	69	1	10
11453110800	3221912238757	8	8	117	75	75	1	10
11453110850	3221912238764	8.5	8.5	117	75	75	1	5
11453110900	3221912238771	9	9	125	81	81	1	5
11453110950	3221912238788	9.5	9.5	125	81	81	1	5
11453111000	3221912238795	10	10	133	87	87	1	5
11453111050	3221912238801	10.5	10.5	133	87	87	1	5
11453111100	3221912238818	11	11				1	5
11453111150	3221912280671	11.5	11.5	142	94	94	1	5
11453111200	3221912238825	12	12	151	101	101	1	5
11453111250	3221912280688	12.5	12.5	151	101	101	1	5
11453111300	3221912238832	13	13	151	101	101	1	5