

TIVOLY 11454170017 | 25 FURIUS FUSIO coated HSS metal drill bits, split point, Ø 1 to 13 mm by 1/2 PREMIUM

Special drilling of steels. Drilling of steels < 950 N/mm², grey cast irons, ductile cast irons, aluminiums. Speed, lifespan. Comfort and precision.



- Especially for high-strength steels and cast irons
- Incredibly fast drilling
- Maximum long life
- Comfort and precision
- Made in France
- Ergonomic rack
- Automatic centring
- 35° type N flute
- High-speed steel
- 135° tip

Ø 1 - 1.5 - 2 - 2.5 - 3 - 3.5 - 4 - 4.5 - 5 - 5.5 - 6 - 6.5 - 7 - 7.5 - 8 - 8.5 - 9 - 9.5 - 10 - 10.5- 11 - 11.5 - 12 - 12.5 - 13 mm - TIVOLY BOX Case





Machine













Application











Features

























Properties and benefits

- + Ergonomic rack: the maximum number of tools in the minimum amount of space, with excellent support for the products and perfect legibility of the dimensions. Simple gripping of the tools and optimal hold, preventing the products moving around during transport or in the event that the case is dropped./
- + Split-point grinding:reduction of the drill tip.

 Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the requried axial load.
- 🕂 35° type N flute: normal flute profile with a 35° helix angle. 🥯 Suitable for strong and difficult materials. Enables finer edge sharpness, for reduced cutting effort.
- High-speed steel: HSS substrate ♥ For general use in steels and cast irons up to 950 N/mm²
- 135° tip: 135° tip angle for the sharpening of the drill bit. 🕏 Suitable for strong and difficult materials. Enables a shorter and stronger cutting edge, thus prolonging the service life.
- 🕂 FUSIO coating: Ti2CN base, thickness 2/4µm, hardness 3200HV, coefficient of friction 0.2, heat resist. 400°C. 🕏 Thermal shield. Allows you to significantly increase service life, cutting speed, and progress. Reduces the axial load. Especially for steels.

Données de gestion :

PCB: 1 / Kilogram.: 1,080 / Dimensions: 0180x0170x0060 mm / EAN: 3221912044853