

The must-have tool for drilling and screwing very close to walls and in tight spaces. Ball shaft that can pivot about 20°.

- Quick-change shank
- Quick-change head
- Swivel ball joint shaft
- Vertical locking
- Retaining ring



Features



Properties and benefits

- + Quick-Change hex attachment: a hexagonal recessed attachment for the quick locking and unlocking of the bit. Compliant with the DIN 3126 E6.3 standard ➡ Enables the quick changing of your bits by doing away with the manual tightening/loosening of the chuck. For drills and screwdrivers.
- + 6,35 mm Quick-Change hex head: a hexagonal recessed attachment for the quick locking and unlocking of the bit. Compliant with the DIN 3126 E6.3 standard ➡ Enables the quick changing of your bits by doing away with the manual tightening/loosening of the chuck. For drills and screwdrivers.
- + Swivel ball joint shaft that can pivot about 360° with a 20° angle ➡ For drilling and screwing in a straight position or very close to walls and in tight spaces.
- + Vertical locking ➡ Enables the use of the bit holder in the classic straight position.
- + Tubular non-rotational retaining ring, ➡ Allows you to hold the bit holder with your fingers for safe and convenient positioning when screwing or drilling.

Données de gestion :

PCB : 1 / Kilogram. : 0,068 / Dimensions : 0150x0050x0015 mm / EAN : 3221912142252