

The torsion effect bit to prevent premature breakage and wear. It dampens the tightening torques at the end of the screwing.



- Breakage-resistant tool
- 6.35 mm hexagonal shank
- With colored ring
- Torsion breakage-resist.



#### Machine



#### Features



#### Properties and benefits

- + 6.35 mm hexagonal shank / DIN 3126 C 6.3 standard: geometric characteristics comply with dimensional standards. ➡ Enables a perfect hold with bit-holders.
- + With different color rings depending on the screw heads ➡ For the simple and fast recognition of screw head types. Each screw head has its own colour code
- + Break-resistant twist: reduced central geometry and special thermal treatment that absorbs peak screwing forces and extreme torque variations. ➡ Prevents the premature breakage of the bit, as well as its premature wear, for a longer service life.



Code	EAN	N°	Ø Screw	L	Max Torque Nmm	QTY	PCB
11520220001	3221910879785	N1-2-3	2,5-3/3,5-5/5,5-7	25		3	1
11520220100	3221910866990	N1	2,5-3	25		2	6
11520220200	3221910867003	N2	3,5-5	25		2	6



## 1152022 | Screwdriver bit -Torsion - For Pozidriv screws ESSENTIAL (Blister)

The torsion effect bit to prevent premature breakage and wear. It dampens the tightening torques at the end of the screwing.

11520220300	3221910867010	N3	5,5-7	25	2	6
-------------	---------------	----	-------	----	---	---