

The torsion effect bit to prevent premature breakage and wear. It dampens the tightening torques at the end of the screwing.



- Breakage-resistant tool
- Maximum torque transmission

- 6.35 mm hexagonal shank
- With colored ring
- Torsion breakage-resist.



Machine




Features



Properties and benefits

- + 6.35 mm hexagonal shank / DIN 3126 C 6.3 standard: geometric characteristics comply with dimensional standards. ➡ Enables a perfect hold with bit-holders.
- + With different color rings depending on the screw heads ➡ For the simple and fast recognition of screw head types. Each screw head has its own colour code
- + Break-resistant twist: reduced central geometry and special thermal treatment that absorbs peak screwing forces and extreme torque variations. ➡ Prevents the premature breakage of the bit, as well as its premature wear, for a longer service life.



Code	EAN	N°	Ø Screw	L	Max Torque Nmm	QTY	PCB
11520520001	3221910867157	N20-25-30	4-4,2/5-5,5/6-6,3	25		3	1
11520520002	3221912108623	N8-10-15		25		3	1
11520521000	3221910867164	N10	3-3,5	25		1	6
11520521500	3221910867171	N15	3,5-3,9	25		1	6
11520522000	3221910867188	N20	4-4,2	25		1	6
11520522500	3221910867195	N25	5-5,5	25		1	6
11520523000	3221910867218	N30	6-6,3	25		1	6
11520524000	3221910867225	N40	8	25		1	6