

The Torsion TiN bit for intensive screwing. TiN coating to prevent premature wear. Torsion effect.



- Breakage-resistant tool
- Maximum long life
- Intensive and repetitive work
  
- 6.35 mm hexagonal shank
- With colored ring
- TiN coating
- Torsion breakage-resist.



#### Machine



#### Features



#### Properties and benefits

- + 6.35 mm hexagonal shank / DIN 3126 C 6.3 standard: geometric characteristics comply with dimensional standards. ➡ Enables a perfect hold with bit-holders.
- + With different color rings depending on the screw heads ➡ For the simple and fast recognition of screw head types. Each screw head has its own colour code
- + TiN coating: surface treated with titanium nitride, for resistance to wear. ➡ Enables greater longevity of the screwdriver bit and protection against corrosion.
- + Break-resistant twist: reduced central geometry and special thermal treatment that absorbs peak screwing forces and extreme torque variations. ➡ Prevents the premature breakage of the bit, as well as its premature wear, for a longer service life.



Code	EAN	N°	Ø Screw	L	Max Torque Nmm	QTY	PCB
11522521000	3221910867690	N10	3-3,5	25		1	3
11522521500	3221910867706	N15	3,5-3,9	25		1	3
11522522000	3221910867713	N20	4-4,2	25		1	3
11522522500	3221910867720	N25	5-5,5	25		1	3
11522522700	3221912061119	N27	4,3-5	25		1	3
11522523000	3221910867737	N30	6-6,3	25		1	3
11522524000	3221910867744	N40	8	25		1	3