

Drill bit for the rotation drilling of various types of TILE/STONEWARE materials, thanks to its diamond tungsten carbide coating and its water lubrication.



- **Water lubrication**
- **Anti-rotation attachment**
- **6.35 mm hexagonal shank**
- **Diamond depositing**
- **Wet drilling**



#### Machine



#### Application



#### Features



#### Properties and benefits

- + 6.35 mm hexagonal shank / DIN 3126 C 6.3 standard: geometric characteristics comply with dimensional standards. ➡ Enables a perfect hold with bit-holders.
- + Depositing of diamond grains by means of electrolysis. ➡ Enables the drilling of hard materials.
- + Wet drilling: is used with the guide with an integrated water tank, to cool the cutting area and protect the diamond grains. ➡ Continual irrigation optimises drilling and extends the life of the tool.



Code	EAN	Ø	d2/CM	L	I	lu	QTY	PCB
12000820500	3221912064851	5	6.35	55	30	1	1	
12000820600	3221912064868	6	6.35	55	30	1	3	
12000820700	3221912064875	7	6.35	55	30	1	1	
12000820800	3221912064882	8	6.35	55	30	1	3	
12000821000	3221912064899	10	6.35	55	30	1	3	
12000821200	3221912065001	12	6.35	55	30	1	1	
12000822500	3221912065018	25	6.35	55	30	1	1	