

# 1T50242 | Jigsaw blade - For worktop - T attachment TECHNIC (Blister)

Bi-metal, the perfect combination of flexibility (HSS "spring" steel), and durability (welded HSS teeth). Head treated in a vacuum furnace. Suitable for wood & metal working.



- Cross ground, tapered
- Inverted tothing
- HSS tothing



### Machine




### Application



Worktop

### Features



### Properties and benefits

- + Cross ground, tapered: each tooth is perpendicular to the cutting axis, is aligned, and cuts along its entire width. The sides and the back are tapered. ⤵ Enables fast and straight cutting. The blade does not come back into contact with the material and enables a fine and clean cut.
- + Inverted tothing: blade whereby the teeth cut while moving downward. Inverted teeth: blade whereby the teeth cut while moving downwards. ⤵ Enables clean cuts without splinters on the top side. For an optimal result, disable the machine's pendulum function.
- + Bi-metal steel blade: combination of progressive tothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ⤵ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.



Code	EAN	Cutting thickness	Cutting type	Sawing cutting quality	L	I	Pitch	QTY	PCB
XT505520012	3221910898557	3-50	Straight cut	Finishing	100	75	2	3	