

1T50382 | Jigsaw blade - Double tootinging - For laminated wood - U attachment **TECHNIC (Blister)**

High-alloy vanadium chrome steel is used for working on softer materials such as wood, fiberboard panels, and synthetic materials.



- Cross ground, tapered
- Double tootinging
- Carbon steel toothing
- Variable teeth



Machine



Application



Features



Properties and benefits

- + Cross ground, tapered: each tooth is perpendicular to the cutting axis, is aligned, and cuts along its entire width. The sides and the back are tapered. ➡ Enables fast and straight cutting. The blade does not come back into contact with the material and enables a fine and clean cut.
- + Double toothing: blade with a double cutting edge, thanks to its teeth running all the way around. ➡ Enables cutting in any direction, without turning your saw around. You save time and energy, for optimal comfort.
- + Blade made from HCS carbon steel: high-strength carbon steel ideal for cutting into soft wood and non-abrasive carpentry materials. ➡ Enables longer service life thanks to the flexibility of the blade.
- + Variable toothing: design whereby the teeth are positioned with irregular gaps (pitches) and with alternating small and large teeth with different gap sizes. ➡ Enables the cutting of a wide range of different materials. Reduces the risk of teeth breaking and reduces vibrations when cutting.



Code	EAN	Cutting thickness	Cutting type	Sawing cutting quality	L	I	Pitch	QTY	PCB
XT505326003	3221912082725	60	Curve & Straight cut	Finishing	115	95	2	2	1