


**1T50482 | Jigsaw blade - For plastic, Plexiglass and epoxy  
- U attachment **TECHNIC** (Blister)**

Bi-metal, the perfect combination of flexibility (HSS "spring" steel), and durability (welded HSS teeth). Head treated in a vacuum furnace. Suitable for wood & metal working.




- Milled, set
- HSS toothing



**Machine**



**Application**



**Features**



**Properties and benefits**

- + Milled, set: blade for somewhat crude cutting into hard and soft wood, aluminium, plastic materials, and non-ferrous metals. ➡ Enables the rapid progression of the blade into hard and soft wood, aluminium, plastic materials, and non-ferrous metals.
- + Bi-metal steel blade: combination of progressive toothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ➡ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.



| Code        | EAN           | Cutting thickness | Cutting type | Sawing cutting quality | L  | I  | Pitch | QTY | PCB |
|-------------|---------------|-------------------|--------------|------------------------|----|----|-------|-----|-----|
| XT505326010 | 3221912082800 | 4                 | Straight cut | Finishing              | 75 | 50 | 2     | 1   |     |