

1T50592 | Jigsaw blade - For parquet - U attachment TECHNIC (Blister)

Bi-metal, the perfect combination of flexibility (HSS "spring" steel), and durability (welded HSS teeth). Head treated in a vacuum furnace. Suitable for wood & metal working.



- Cross ground, tapered
- Pointed toothing
- HSS toothing



Machine




Application



Parquet

Features



Properties and benefits

- + Cross ground, tapered: each tooth is perpendicular to the cutting axis, is aligned, and cuts along its entire width. The sides and the back are tapered. ➡ Enables fast and straight cutting. The blade does not come back into contact with the material and enables a fine and clean cut.
- + Pointed toothing: design whereby the teeth are positioned horizontally to the body of the blade. ➡ Enables clean cutting quality, with no splinters on either side. For an optimal result, disable the machines pendulum function.
- + Bi-metal steel blade: combination of progressive toothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ➡ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.



| Code | EAN | Cutting thickness | Cutting type | Sawing cutting quality | L | I | Pitch | QTY | PCB |
|-------------|---------------|-------------------|--------------|------------------------|-----|----|-------|-----|-----|
| XT505320039 | 3221910898168 | 3-30 | Straight cut | Finishing | 100 | 75 | 2 | 3 | |
| XT505320040 | 3221910898175 | 1.5-15 | Curved cut | Finishing | 100 | 75 | 2 | 3 | |