


Tap for inserting into steels, stainless steels, aluminium.



- Threading of standard Steels
- Spiral flute
- 5% cobalt HSS

Machine



Application



P1- Unrealized steels
P2- Weakly allied steels

Features



Properties and benefits

- + Spiral flute : A flute shape that allows chips to be evacuated through the entrance to the hole. ↻ Allows better heat resistance due to better chip evacuation. For blind holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ↻ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960057100300050	3221912250735	M-EG 3	0.5	TivolyNorm	3,15	63	12	2-3	3,40	1	1	
960057100400070	3221912250742	M-EG 4	0.7	TivolyNorm	4,20	70	14	2-3	4,90	1	1	
960057100500080	3221912250759	M-EG 5	0.8	TivolyNorm	5,25	80	16	2-3	4,90	1	1	
960057100600100	3221912250766	M-EG 6	1	TivolyNorm	6,30	90	18	2-3	6,20	1	1	
960057100800125	3221912250773	M-EG 8	1.25	TivolyNorm	8,40	100	20	2-3	8,00	1	1	
960057101000150	3221912250780	M-EG 10	1.5	TivolyNorm	10,40	110	22	2-3	7,00	1	1	
960057101200175	3221912250797	M-EG 12	1.75	TivolyNorm	12,50	110	25	2-3	9,00	1	1	