

**9602121 | Machine tap HSS-E5 (cobalt 5%) -M -DIN 371 -B
Shape (GUN) -4H**


Tap for steel, stainless steel and aluminium. Particularly suitable for through tapping thanks to its Gun entry.



- **Precise thread tapping**
- **Threading of standard Steels**

- **GUN entry**
- **5% cobalt HSS**

Machine



Application



P1-
Unrealized
steels

P2-
Weakly
allied
steels

Features



Properties and benefits

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. ➡ Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960212100300050	3221912200013	M 3	3	0.5	DIN 371	2,50	56	10	4-4.5	2,70	1	1
960212100400070	3221912190215	M 4	4	0.7	DIN 371	3,30	63	12	4-4.5	3,40	1	1
960212100500080	3221910928698	M 5	5	0.8	DIN 371	4,20	70	12	4-4.5	4,90	1	1
960212100600100	3221912240828	M 6	6	1	DIN 371	5,00	80	15	4-4.5	4,90	1	1
960212100800125	3221912240835	M 8	8	1.25	DIN 371	6,75	90	18	4-4.5	6,20	1	1
960212101000150	3221910928704	M 10	10	1.5	DIN 371	8,50	100	22	4-4.5	8,00	1	1