

**9606021 | Machine tap HSSE-PM -M MF -DIN 374/376 -B
Shape (GUN) -6H -Dulofix shank**

Tap (sintered steel) for steels. Particularly suitable for through tapping thanks to its Gun entry.




- Especially for high-strength steels, stainless steels and cast irons
- GUN entry

Machine



Application



Features



Properties and benefits

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes. ➔



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960602100400070	8420609323515	M	4	0,7	DIN 376	3,30	63	12	4-4.5	2,10	1	1
960602100500080	8420609323522	M	5	0,8	DIN 376	4,20	70	14	4-4.5	2,70	1	1
960602100600100	8420609323539	M	6	1	DIN 376	5,00	80	16	4-4.5	3,40	1	1
960602100800125	8420609323560	M	8	1,25	DIN 376	6,75	90	18	4-4.5	4,90	1	1
960602101000150	8420609323607	M	10	1,5	DIN 376	8,50	100	20	4-4.5	5,50	1	1
960602101200175	8420609323652	M	12	1,75	DIN 376	10,25	110	22	4-4.5	7,00	1	1
960602101400200	8420609323683	M	14	2	DIN 376	12,00	110	25	4-4.5	9,00	1	1
960602101600200	8420609323713	M	16	2	DIN 376	14,00	110	28	4-4.5	9,00	1	1
960602101800250	8420609323737	M	18	2,5	DIN 376	15,50	125	32	4-4.5	11,00	1	1
960602100800100	8420609323553	MF	8	1	DIN 374	7,00	90	18	4-4.5	4,90	1	1
960602101000100	8420609323584	MF	10	1	DIN 374	9,00	90	18	4-4.5	5,50	1	1
960602101200150	8420609323645	MF	12	1,5	DIN 374	10,50	100	22	4-4.5	7,00	1	1
960602101400150	8420609323676	MF	14	1,5	DIN 374	12,50	100	22	4-4.5	9,00	1	1
960602101800150	8420609558221	MF	18	1,5	DIN 374	16,50	110	25	4-4.5	11,00	1	1