

**9606051 | Standard machine tap HSSE-PM -M -DIN 374/376 -C Shape -6H -Dulofix shank**

Tap (sintered steel) for steels. Particularly suitable for blind taps due to its helical flute.



- Especially for high-strength steels, stainless steels and cast irons
- Spiral flute

**Machine**



**Application**

P  
1

P1- Unrealized steels

P  
2

P2- Weakly allied steels

P  
3

P3- strong alloy steels

**Features**

M

6H

FORM  
C

35°

HSS-E  
PM

BRIGHT  
UNCOATED

DIN  
374/376

CYL+

2-2x P16

**Properties and benefits**

- +
  - +
- Spiral flute : A flute shape that allows chips to be evacuated through the entrance to the hole. ↻ Allows better heat resistance due to better chip evacuation. For blind holes.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960605100800125	8420609324253	M 8	8	1,25	DIN 376	6,75	90	12	2-2.5	4,90	1	1
960605101000150	8420609324307	M 10	10	1,5	DIN 376	8,50	100	14	2-2.5	5,50	1	1
960605101200175	8420609324345	M 12	12	1,75	DIN 376	10,25	110	16	2-2.5	7,00	1	1