

Tap (sintered steel) for steels, stainless steels and refractory alloys. Particularly suitable for through tapping thanks to its Gun entry.




- Especially for stainless steels
- GUN entry
- STEAM treatment

Machine



Application



Features



Properties and benefits

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. → Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.
- + STEAM treatment : Steam oxidation treatment. → Avoids cold bonding. Reduced coefficient of friction in steels.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960682100600100	8420609328183	M 6	6	1	DIN 376	5,00	80	16	4-4.5	3,40	1	1
960682100800125	8420609328213	M 8	8	1,25	DIN 376	6,75	90	18	4-4.5	4,90	1	1
960682101000150	8420609328244	M 10	10	1,5	DIN 376	8,50	100	20	4-4.5	5,50	1	1
960682101200175	8420609328282	M 12	12	1,75	DIN 376	10,25	110	22	4-4.5	7,00	1	1
960682101400200	8420609328305	M 14	14	2	DIN 376	12,00	110	25	4-4.5	9,00	1	1
960682101600200	8420609328329	M 16	16	2	DIN 376	14,00	110	28	4-4.5	9,00	1	1
960682101800250	8420609328343	M 18	18	2,5	DIN 376	15,50	125	32	4-4.5	11,00	1	1
960682102000250	8420609328350	M 20	20	2,5	DIN 376	17,50	140	32	4-4.5	12,00	1	1
960682102400300	8420609328398	M 24	24	3	DIN 376	21,00	160	32	4-4.5	14,50	1	1
960682100800100	8420609328206	MF 8	8	1	DIN 374	7,00	90	18	4-4.5	4,90	1	1
960682101000100	8420609328220	MF 10	10	1	DIN 374	9,00	90	18	4-4.5	5,50	1	1
960682101200150	8420609328275	MF 12	12	1,5	DIN 374	10,50	100	22	4-4.5	7,00	1	1
960682101400150	8420609328299	MF 14	14	1,5	DIN 374	12,50	100	22	4-4.5	9,00	1	1
960682101600150	8420609328312	MF 16	16	1,5	DIN 374	14,50	110	22	4-4.5	9,00	1	1