

**960ARG1 | Multi-application machine tap HSSE-PM -CrN
Plus coated -M-MF -DIN 371/374/376 -Thread-former -6GX
-Grooved PREMIUM (Unit packaging)**

Application: Through/blind hole < 3xØ in long-chipping non-ferrous alloys



- Especially for aluminium
- Precise thread tapping

Machine




Application



N- Non-ferrous alloys

Features



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960ARG100300050	3221912217240	M 3	3	0.5	DIN 371	2,81	56	10	3.5	2,70	1	1
960ARG100400070	3221912217257	M 4	4	0.7	DIN 371	3,72	63	12	4.5	3,40	1	1
960ARG100500080	3221912217264	M 5	5	0.80	DIN 371	4,67	70	12	6	4,90	1	1
960ARG100600100	3221912217271	M 6	6	1	DIN 371	5,60	80	15	6	4,90	1	1
960ARG100800125	3221912217318	M 8	8	1.25	DIN 371	7,47	90	18	8	6,20	1	1
960ARG101000150	3221912217295	M 10	10	1.5	DIN 371	9,34	100	22	10	6,20	1	1
960ARG101200175	3221912217301	M 12	12	1.75	DIN 371374376	11,25	110	22	9	7,00	1	1