

High performance tap designed for brass and copper alloys.



- **Special Bronzes and Brasses**
- **Made in Spain**
  
- **5% cobalt HSS**

**Machine**



**Application**



N3-2-  
Copper-  
brass alloy  
with pb ≤  
1%

N3-4-  
Copper-  
Bronze  
Alloy

**Features**



**Properties and benefits**

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) → For general use in metals up to 1200 N/mm<sup>2</sup>.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960BT1100300050	8420609526480	M 3	3	0,5	DIN 371	2,50	56	10	2-3	2,70	1	1
960BT1100400070	8420609526497	M 4	4	0,7	DIN 371	3,30	63	12	2-3	3,40	1	1
960BT1100500080	8420609526503	M 5	5	0,8	DIN 371	4,20	70	14	2-3	4,90	1	1
960BT1100600100	8420609526510	M 6	6	1	DIN 371	5,00	80	16	2-3	4,90	1	1
960BT1100800125	8420609526527	M 8	8	1,25	DIN 371	6,75	90	18	2-3	6,20	1	1
960BT1101000150	8420609526534	M 10	10	1,5	DIN 371	8,50	100	20	2-3	8,00	1	1
960BT1101200175	8420609526541	M 12	12	1,75	DIN 376	10,25	110	22	2-3	7,00	1	1
960BT1101400200	8420609526558	M 14	14	2	DIN 376	12,00	110	25	2-3	9,00	1	1
960BT1101600200	8420609526565	M 16	16	2	DIN 376	14,00	110	28	2-3	9,00	1	1
960BT1100800100	8420609596209	MF 8	8	1	DIN 371	7,00	90	18	2-3	6,20	1	1
960BT1101000100	8420609596216	MF 10	10	1	DIN 374	9,00	90	18	2-3	8,00	1	1
960BT1101200150	8420609596223	MF 12	12	1,5	DIN 374	10,50	100	22	2-3	7,00	1	1
960BT1101400150	8420609596230	MF 14	14	1,5	DIN 374	12,50	100	22	2-3	9,00	1	1