

960SRG1 | Multi-application machine tap HSSE-PM -TiN 20 coated -M -DIN 371/376 -Thread-former -6GX -Grooved

"By deformation" tap (sintered steel) for steels, stainless steels and cast iron. TiN 20 coating gives it an increased service life and high resistance to abrasion.



- Especially for high-strength steels, stainless steels and cast irons
- Precise thread tapping
- Made in Spain

- TiN20 coating

Machine



Application



Features



Properties and benefits

- + TiN20 coating : Hardness 2300HV, coefficient of friction 0,60, resistance to heat (600°C). ↻ Very high abrasion resistance. Increased tool life.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960SRG100300050	3221912216823	M 3	3	0.5	DIN 371	2,80	56	10	2-2.5	2,70	1	1
960SRG100400070	3221912216830	M 4	4	0.7	DIN 371	3,70	63	12	2-2.5	3,40	1	1
960SRG100500080	3221912216847	M 5	5	0.8	DIN 371	4,65	70	12	2-2.5	4,90	1	1
960SRG100600100	3221912216854	M 6	6	1	DIN 371	5,60	80	15	2-2.5	4,90	1	1
960SRG100800125	3221912216861	M 8	8	1.25	DIN 371	7,40	90	18	2-2.5	6,20	1	1
960SRG101000150	3221912216878	M 10	10	1.5	DIN 371	9,30	100	22	2-2.5	8,00	1	1
960SRG101200175	3221912216885	M 12	12	1.75	DIN 376	11,20	110	22	2-2.5	7,00	1	1