

960ST91 | FLASHCUT multi-application machine tap HSS-E-PM -TiN coated -M MF -DIN 371/374/376 -Thread-former -6HX -Grooved

High performance "by deformation" tap (sintered steel) for steels. TiN coating increases the cutting conditions and the tool life.



- Made in Spain
- Precise and long-lasting thread tapping

- TiN coating

Machine



Application



Features



Properties and benefits

- + TiN coating: TiN base, thickness 2/4µm, hardness 2300HV, coefficient of friction 0.4, heat resistance 600°C. Protects against abrasion, oxidation, adhesion. ⚙ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. General use.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960ST9100300050	8420609527142	M	3	0,5	DIN 371	2,80	56	10	2.5	2,70	1	1
960ST9100400070	8420609527159	M	4	0,7	DIN 371	3,40	63	12	2.5	3,40	1	1
960ST9100500080	8420609527166	M	5	0,8	DIN 371	4,65	70	14	2.5	4,90	1	1
960ST9100600100	8420609527173	M	6	1	DIN 371	5,60	80	16	2.5	4,90	1	1
960ST9100800125	8420609527180	M	8	1,25	DIN 376	7,40	90	18	2.5	6,20	1	1
960ST9101000150	8420609527197	M	10	1,5	DIN 371	9,30	100	20	2.5	8,00	1	1
960ST9101200175	8420609527203	M	12	1,75	DIN 376	11,20	110	22	2.5	7,00	1	1
960ST9101400200	8420609527210	M	14	2	DIN 376	13,00	110	25	2.5	9,00	1	1
960ST9101600200	8420609527227	M	16	2	DIN 376	15,00	110	28	2.5	9,00	1	1
960ST9100800100	8420609596476	MF	8	1	DIN 371	7,50	90	18	2.5	6,20	1	1
960ST9101000100	8420609596483	MF	10	1	DIN 371	9,50	90	18	2.5	8,00	1	1
960ST9101200150	8420609596490	MF	12	1,5	DIN 374	11,30	100	22	2.5	7,00	1	1
960ST9101400150	8420609596506	MF	14	1,5	DIN 374	13,30	100	22	2.5	9,00	1	1