

**9612011 | Standard machine tap HSS-E5 (cobalt 5%) -BSW  
-DIN 371 -Straight -Reinforced shank**

Tap for short-chipping metals. Reinforced tail. Profile: BSW.



- Threading of standard Steels
- 5% cobalt HSS

**Machine**



**Application**



P1- Unrealized steels

P2- Weakly allied steels

**Features**



**Properties and benefits**

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm<sup>2</sup>.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
961201100180400	8420609336294	BSW	1/8"	40	DIN 371	2,55	56	11	2-3	2,70	1	1
961201100532320	8420609336355	BSW	5/32"	32	DIN 371	3,20	63	12	2-3	3,40	1	1
961201100140200	8420609336270	BSW	1/4"	20	DIN 371	5,10	80	16	2-3	5,50	1	1
961201100516180	8420609336331	BSW	5/16"	18	DIN 371	6,50	90	18	2-3	6,20	1	1
961201100380160	8420609336317	BSW	3/8"	16	DIN 371	7,90	90	18	2-3	7,00	1	1