

High performance tap for brass and copper alloys. Profile: UNC UNF.



■ 5% cobalt HSS

**Machine**



**Application**



N3-2-  
Copper-  
brass alloy  
with pb ≤  
1%

N3-4-  
Copper-  
Bronze  
Alloy

**Features**



**Properties and benefits**

+ 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) → For general use in metals up to 1200 N/mm<sup>2</sup>.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
962BT1100140200	8420609614941	UNC 1/4"	20	DIN 371	5,10	80	16	2-3	5,50	1	1	
962BT1100380160	8420609614989	UNC 3/8"	16	DIN 371	7,90	90	18	2-3	7,00	1	1	
962BT1100120130	8420609614927	UNC 1/2"	13	DIN 376	10,50	110	25	2-3	6,20	1	1	
962BT1100340100	8420609614965	UNC 3/4"	10	DIN 376	16,50	125	32	2-3	11,00	1	1	
962BT1100140280	8420609614958	UNF 1/4"	28	DIN 371	5,50	80	16	2-3	4,90	1	1	
962BT1100380240	8420609614996	UNF 3/8"	24	DIN 371	8,50	100	18	2-3	5,50	1	1	
962BT1100120200	8420609614934	UNF 1/2"	20	DIN 376	11,50	110	25	2-3	7,00	1	1	
962BT1100340160	8420609614972	UNF 3/4"	16	DIN 376	17,50	125	32	2-3	11,00	1	1	
962BT110000120	8420609615016	UNF 1"	12	DIN 376	23,25	140	32	2-3	16,00	1	1	