


# 962CT11 | FLASHCUT machine tap HSSE-PM -TiCN coated -UNC UNF -DIN 371/376 -Straight -2B

High performance tap (sintered steel) for cast iron. TiCN-MP coating increases tool life and reduces the coefficient of friction. Profile: UNC UNF.



- Especially for cast irons
- Made in Spain
- TiCN coating

## Machine



## Application



K- Ferrous  
Cast iron  
with Short  
Chips

## Features



## Properties and benefits

- + TiCN coating : Thickness 2/4µm, hardness 3500 HV, coefficient of friction 0,15, resistance to heat (400°C). High toughness while maintaining a very high hardness. Reduced coefficient of friction. Increased tool life. Special steels.



| Code            | EAN           | Thread | Ø    | Pitch | Norm    | Drill | L   | I  | I4  | I5    | QTY | PCB |
|-----------------|---------------|--------|------|-------|---------|-------|-----|----|-----|-------|-----|-----|
| 962CT1100140200 | 8420609615047 | UNC    | 1/4" | 20    | DIN 371 | 5,10  | 80  | 16 | 2-3 | 5,50  | 1   | 1   |
| 962CT1100380160 | 8420609615085 | UNC    | 3/8" | 16    | DIN 371 | 7,90  | 90  | 18 | 2-3 | 7,00  | 1   | 1   |
| 962CT1100120130 | 8420609615023 | UNC    | 1/2" | 13    | DIN 376 | 10,50 | 110 | 25 | 2-3 | 6,20  | 1   | 1   |
| 962CT1100340100 | 8420609615061 | UNC    | 3/4" | 10    | DIN 376 | 16,50 | 125 | 32 | 2-3 | 11,00 | 1   | 1   |
| 962CT1110000080 | 8420609615108 | UNC    | 1"   | 8     | DIN 376 | 22,00 | 160 | 36 | 2-3 | 16,00 | 1   | 1   |
| 962CT1100140280 | 8420609615054 | UNF    | 1/4" | 28    | DIN 371 | 5,50  | 80  | 16 | 2-3 | 4,90  | 1   | 1   |
| 962CT1100380240 | 8420609615092 | UNF    | 3/8" | 24    | DIN 371 | 8,50  | 100 | 18 | 2-3 | 5,50  | 1   | 1   |
| 962CT1100120200 | 8420609615030 | UNF    | 1/2" | 20    | DIN 376 | 11,50 | 110 | 25 | 2-3 | 7,00  | 1   | 1   |
| 962CT1100340160 | 8420609615078 | UNF    | 3/4" | 16    | DIN 376 | 17,50 | 125 | 32 | 2-3 | 11,00 | 1   | 1   |
| 962CT1110000120 | 8420609615115 | UNF    | 1"   | 12    | DIN 376 | 23,25 | 140 | 32 | 2-3 | 16,00 | 1   | 1   |