

9633451 | Machine taps MULTI-APPLICATION HSSE VAPORISED| BSP GAS thread | DIN 5156 | Form B TECHNIC (Unit packaging)

Application: Through hole in steels up to 1000N/mm², stainless steels and cast iron.



- Especially for multiple applications
- 5% cobalt HSS

Machine



Application



Features



Properties and benefits

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➔ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
963345100120140		BSPG	1/2"	14	DIN 5156	19,00	125	25	2>3	12,00	1	1
963345100140190		BSPG	1/4"	19	DIN 5156	11,80	100	22	2>3	9,00	1	1
963345100180280	3221912164506	BSPG	1/8"	28	DIN 5156	8,80	90	18	2>3	5,50	1	1
963345100380190		BSPG	3/8"	19	DIN 5156	15,25	100	25	2>3	9,00	1	1
963345110000110	3221912172532	BSPG	1"	11	DIN 5156	30,75	140	28	2>3	20,00	1	1
963345110140110	3221912267603	BSPG	1"1/4	11	DIN 5156	39,50	160	36	2>3	24,00	1	1
963345100340140		BSPG	3/4"	14	DIN 5156	24,50	125	25	2>3	16,00	1	1
963345110120110	3221912267610	BSPG	1/2"	11	DIN 5156	45,50	190	32	2>3	29,00	1	1