


**963CT11 | Flashcut machine tap HSSE-PM -TiCN coated
-BSP G -DIN 5156 -Straight -6H**

High performance tap (sintered steel) for cast iron. TiCN-MP coating increases tool life and reduces the coefficient of friction. Profile: BSP G.



- Especially for cast irons
- TiCN coating

Machine



Application



K- Ferrous
Cast iron
with Short
Chips

Features



Properties and benefits

- + TiCN coating : Thickness 2/4µm, hardness 3500 HV, coefficient of friction 0,15, resistance to heat (400°C). High toughness while maintaining a very high hardness. Reduced coefficient of friction. Increased tool life. Special steels.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
963CT1100180280	8420609615641	BSPG 1/8"	28	DIN 5156	8,80	90	18	2-3	5,50	1	1	
963CT1100140190	8420609615634	BSPG 1/4"	19	DIN 5156	11,80	100	22	2-3	9,00	1	1	
963CT1100380190	8420609615665	BSPG 3/8"	19	DIN 5156	15,30	100	25	2-3	9,00	1	1	
963CT1100120140	8420609615627	BSPG 1/2"	14	DIN 5156	19,00	125	25	2-3	12,00	1	1	
963CT1100340140	8420609615658	BSPG 3/4"	14	DIN 5156	24,50	140	28	2-3	16,00	1	1	
963CT1110000110	8420609615672	BSPG 1"	11	DIN 5156	30,80	160	36	2-3	20,00	1	1	