


Tap for steel. Passing tail.



- Threading of standard Steels
- 5% cobalt HSS

Machine



Application



Features



Properties and benefits

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➔ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
970460100300050	8420609615689	M 3	3	0,5	NFE 66112	2,50	90	19	4-4.5	1,60	1	1
970460100400070	8420609615696	M 4	4	0,7	NFE 66112	3,30	100	20	4-4.5	2,30	1	1
970460100500080	8420609615702	M 5	5	0,8	NFE 66112	4,20	110	25	4-4.5	3,00	1	1
970460100600100	8420609615719	M 6	6	1	NFE 66112	5,00	120	27	4-4.5	3,50	1	1
970460100800125	8420609615726	M 8	8	1,25	NFE 66112	6,75	135	32	4-4.5	5,00	1	1
970460101000150	8420609615733	M 10	10	1,5	NFE 66112	8,50	150	38	4-4.5	6,00	1	1
970460101200175	8420609615740	M 12	12	1,75	NFE 66112	10,25	165	43	4-4.5	7,00	1	1
970460101400200	8420609615757	M 14	14	2	NFE 66112	12,00	180	50	4-4.5	8,00	1	1
970460101600200	8420609615764	M 16	16	2	NFE 66112	14,00	190	50	4-4.5	10,00	1	1