

# XT50034 | Circular saw blade - Finishing - For hardwood, laminated wood, parquet - For portable saw ESSENTIAL (Carton sleeve)

Perfectly adapted for precise and careful sawing requiring a perfect, cheep-free cutting surface.




- Alternate bevel tooth ATB
- ATB toothing
- Expansion slots
- Anti-kickback heel



## Machine



## Application



## Features



## Properties and benefits

- + Alternate bevel teeth (ATB): bevelled teeth on the upper side, alternatively on the right and on the left. → Ideal for longitudinal and transverse cuts. Suitable for universal use in hard and soft woods, chipboard ...
- + ATB toothing with a positive angle of attack. Teeth angled towards the front. → Enables more aggressive work.
- + Expansion slots: these are distributed along the outer edges of the disc. → They allow the metal to expand when it heats as a result of friction, thus avoiding the deformation of the blade.
- + Anti-kickback heel: the presence of an anti-kickback heel is vital. They are located at the back of the teeth. → Limits the quantity of material removed by each tooth of the blade. Thus prevents excessive cutting effort and eliminates wood emissions.



Code	EAN	Blade diameter	d2	Bore	Z	Reduction ring Ø	E1	E2	Max. rotation speed	QTY	PCB
XT50514004164	3221912006400	130	20	30	16	16	1.5	2.45	7500	1	1
XT50514004165	3221912006417	140	20	30	12,7	12,7	1.5	2.45	7500	1	1
XT50514004149	3128820041496	150	20	30	10+16	10+16	1.5	2.45	7500	1	1
XT50514004440	3128820044404	160	20	30	16	16	1.5	2.45	7000	1	1
XT50514004441	3128820044411	160	30	30	20	20	1.5	2.45	7000	1	1
XT50514004412	3128820044121	170	20	30	16	16	1.5	2.45	7000	1	1
XT50514004428	3128820044282	180	20	40	16	16	1.6	2.6	7000	1	1
XT50514004444	3128820044442	180	30	40	20	20	1.6	2.6	7000	1	1
XT50514004179	3128820041793	184	20	40	16	16	1.6	2.6	7000	1	1
XT50514004178	3221912006424	184	30	40	20	20	1.6	2.6	7000	1	1
XT50514004445	3128820044459	190	20	40	16	16	1.7	2.8	7000	1	1
XT50514004183	3128820041830	190	30	40	20	20	1.7	2.8	7000	1	1
XT50514004447	3128820044473	210	30	40	20+25,4	20+25,4	1.7	2.8	6500	1	1
XT50514004449	3221912261076	216	30	48	20	20	1.7	2.55	6500	1	1
XT50514004448	3128820044480	230	30	40	20	20	1.8	2.85	6500	1	1
XT50514004450	3128820044503	235	30	40	25	25	1.8	2.85	6500	1	1
XT50514004451	3221912006448	250	30	48	20	20	1.8	2.85	5500	1	1
XT50514004454	3221912261090	255	30	60	20	20	1.8	2.9	5500	1	1
XT50514004455	3221912362599	165	20	36	16	16	1.5	2.45	7000	1	1