

XT51082 | For wood, MDF, nail-embedded wood, metal - Universal double shank TECHNIC (Carton sleeve)

Cutting of soft wood, construction wood, MDF, wood with embedded nails, metal sheet, metal tubing. The toothing at the end of the blade enables plunge cutting in wood.




- **Maximum long life**
- **X2 universal attachment**
- **Milled, wavy set**
- **8% cobalt steel toothing**



Machine



Application



Features



Properties and benefits

- + Double universal attachment: enables the insertion of the blades into the machine either way round. ↻ Enables the use of either side of the cutting edge of the blade, without changing the blade. Also enables cutting when ascending or descending.
- + Milled, wavy set: the milled wavy toothing maintains a contact surface between the blade and the material. ↻ Prevents jolts and enables very clean cuts into plywood, aluminium, non-ferrous metals and plastic materials.
- + Bi-metal cobalt 8%: combination of teeth made from quick-cutting tempered steel (HSS) enriched with cobalt, and the the body made from HCS. ↻ These blades offer high strength, versatility, and durability. Ideal for intensive work, in the strongest of materials.



Code	EAN	Cutting thickness	Cutting type	Sawing cutting quality	L	I	Pitch	QTY	PCB
XT505820110	3221912213822		Straight cut	Finishing Quick Cut	150	130	2.5 (back 1.8)	2	1